



SFT-150

Salt Capacity : 30 kg

Household : 2-3 people, 1 kitchen, 2 bathrooms

Suitable for apartments

Satisfies most families' basic daily needs

Product Specifications	
Inlet / outlet connections	3/4-inch
Drain pipe connections	Ø13 mm, Ø 16 mm
Weight	≤ 21 kg (net weight, salt excluded)
External dimensions (W x D x H)	470 x 460 x 661 mm



SFT-200

Salt Capacity : 60 kg

Household : 3-5 people, 1-2 kitchens 2 bathrooms

Suitable for houses, villas and light commercial

Satisfies most multi-point water usage

Product Specifications	
Inlet / outlet connections	3/4-inch
Drain pipe connections	Ø13 mm, Ø 16 mm
Weight	≤ 35 kg (net weight, salt excluded)
External dimensions (W x D x H)	483.5 x 482.5 x 1123 mm

models (proposed)	SFT-150	SFT-200
Media cu.ft (L)	0.45 (12.6)	1.0 (28)
Inlet water	city tap water	city tap water
Con. flow rate(MOH)	1.5t/h, 6.6GPM	2t/h, 7.5GPM
flow rate (at 15psi)	2.4t/h, 10.6GPM	2.9t/h, 12.8GPM
work pressure	0.20-0.86MPa	0.20-0.86MPa
recommended pressure	0.25-0.5MPa	0.25-0.5MPa
Temperature	4-39°C	4-39°C
Power	220V/50HZ	220V/50HZ
capacity (grain)	9375	19531
softening water(T) [^]	4.5-6	8.5-11
salt storage(kg)	30kg	60kg
Configuration		
Connection	3/4 "	3/4"
net weight (kg)	≤21	≤35
size (W×D×H)	470 X 460 X 661	483.5 X 482.5 X 1123