



Specification:
 1. Working Pressure: 1.6 MPa;
 2. Working temperature: -10 °C ~ 110 °C;
 3. Surface: Nickel-plated.

Number	Name	Material	Quantity
1	Locking nut	Brass (Cu ≥ 57% Pb ≤ 3.5% Fe ≤ 0.8%) with Nickel plated	1
2	Seal	PTFE	2
3	Ball	Brass (Cu ≥ 57% Pb ≤ 3.5% Fe ≤ 0.8%) with Chrome plated	1
4	Body	Brass (Cu ≥ 57% Pb ≤ 2.8% Fe ≤ 0.8%) with Nickel plated	1
5	Stem	Brass Cu ≥ 57% Pb ≤ 3.5% Fe ≤ 0.8%	1
6	O-ring	NBR	2
7	Handle	Aluminum alloy Surface paint RAL 9017 and Words is white color	1
8	Screw	Steel Q235 with Zn plating	1

Mark	Times	Modification NO	Modification content	Signature	Date
------	-------	-----------------	----------------------	-----------	------

TOLERANCE OF DIMENSIONS AND GEOMETRY UNLESS OTHERWISE SPECIFIED

DIMENSION	GB/T1804-m	ANGLE	PLUMB	CONCENTRICITY
≤ 6	± 0.1	± 1°	± 0.1	Ø 0.3
> 6 ≤ 30	± 0.2			
> 30 ≤ 120	± 0.3			
> 120 ≤ 400	± 0.5			

DESIGN	LL	2013.07.31
CHECKED	XGW	2013.07.31
PROCESSOR	LWF	2013.07.31
STANDARDIZATION	YSY	2013.07.31
APPROVED	YSY	2013.07.31

PRODUCT TYPE:
1500

TITLE:
**Assembly drawing
 1/4"**

ART.
SKS.511

DWG.NO. 2150002		EDITION A	
PROJECTION MEANS S A B	PRIMO ANGLE OF VIEW G.W	DRAWING UNIT mm	SCALE 1.5:1
DESIGN SIGN S A B		N.W. 102.4g	SCALE 1.5:1
PAGE 1 OF 1			
 Email: info@pipelineproductsindia.com Website: www.pipelineproductsindia.com			

Customer drawing number