

CHECK VALVES



RUBBER LINED CHECK VALVES
(FLANGED)
MODEL: B-02

Rubber Lined Check Valves (Flanged) are lined internally with Ebonite Hard rubber so that media does not come in contact with metal. This Model is most suitable for corrosive/erosive applications. The overall dimensions of this valve will be similar to standard Ball NRV but face. To face length will be more by 6-10mm.

DESCRIPTION	MATERIAL OF CONSTRUCTION
BODY/COVER	CAST IRON (GG25)
BALL	NITRILE REINFORCED
SEAT RING	INTEGRAL
FASTENERS	CARBON STEEL
PAINT	ENAMEL PAINT
END CONNECTION	FLANGED
LINING	EBONITE HARD RUBBER FROM INSIDE
SIZE RANGE	25mm TO 350mm
PRESSURE TESTING	BODY: 1.5 X PN SEAT : 1.1 X PN
PRESSURE RATING -KPa	
25mm TO 125mm	PN 1.6
150mm TO 300mm	PN 1.0

350mm

INSTALLATION

FACE TO FACE LENGTH

TEMPERATURE

PN 0.6

HORIZONTAL AS WELL AS VERTICAL

IS 5312 PART I -1984/ DIN 3202-F6 (+6mm)

SUITABLE UPTO 80⁰C

[Home](#) | [About us](#) | [Products](#) | [Gallery](#) | [Documents](#) | [Quality](#) | [Contact / Order](#)