

Weight Chart for VRV Copper Pipes

I T E M	Mtr per 50' coil	Kg per 50' coil
1) Copper Tubes in SOFT bright annealed in 50' COILS		
6.4 mm OD x 0.80 mm (1/4" x 21 Swg)	15.24	1.970
9.5 mm OD x 0.80 mm (3/8" x 21 Swg)	15.24	3.040
12.7 mm OD x 0.80 mm (1/2" x 21 Swg)	15.24	4.220
15.9 mm OD x 0.99 mm (5/8" x 19 Swg)	15.24	6.450
12.7 mm OD x 0.71 mm (1/2" x 22 Swg)	15.24	3.750
15.9 mm OD x 0.71 mm (5/8" x 22 Swg)	15.24	4.760
19.1 mm OD x 0.71 mm (3/4" x 22 Swg)	15.24	5.750
19.1 mm OD x 1.00 mm (3/4" x 19 Swg)	15.24	7.890
6.4 mm OD x 0.71 mm (1/4" x 22 Swg)	15.24	1.780
9.5 mm OD x 0.71 mm (3/8" x 22 Swg)	15.24	2.750
2) Copper tubes in HARD drawn condition in 10' LENGTH		
	Mtr per 10' length	Kg per 10' length
19.1 mm OD x 0.80 mm (3/4" x 21 Swg)	3.05	1.260
22.2 mm OD x 0.80 mm (7/8" x 21 Swg)	3.05	1.490
22.2 mm OD x 1.00 mm (7/8" x 19 Swg)	3.05	1.810
25.4 mm OD x 1.20 mm (1" x 18 Swg)	3.05	2.500
28.6 mm OD x 0.99 mm (1-1/8" x 20 Swg)	3.05	2.340
28.6 mm OD x 1.00 mm (1-1/8" x 19 Swg)	3.05	2.350
31.8 mm OD x 1.10 mm (1-1/4" x 19 Swg)	3.05	2.900
34.9 mm OD x 1.21 mm (1-3/8" x 18 Swg)	3.05	3.560
38.1 mm OD x 1.30 mm (1-1/2" x 18 Swg)	3.05	4.100
41.3 mm OD x 1.43 mm (1-5/8" x 17 Swg)	3.05	4.930

—