

PRODUCT DESCRIPTION : ASHA C.I. PULP VALVES WITH S.S. PLATE , EN-8 SPINDLE

ASHA®

C.I. Pulp Valve



Product Description

C.I. Pulp Valves

Main Body

The main body in two parts will be of C.I. Standard Casting. After machining and shaping it will be bolted together by bolts to make it one piece. To avoid leakage adhesive will be applied before bolting

Gland Plate

The Plate will be of stainless steel

Spindle

The spindle will be of EN - 8 and S.S. material

Legs

The Legs will be of C.I. Standard castings

Wheel

Will be of C.I. Casting

Gland Packing

Will be of C.I. Casting

Packing Support

Will be of C.i. Casting

Spindle Bush

The Spindle Bush will be of Gun Metal Castings

Specification of C.I. Pulp Valves (Rising Spindle)

Valve Size	Main Body	Plate Thickness From	Spindle	Flanged Clearance	Total Length	Wheel
2"	46mm	6mm	6 - 3/4"	6"	14 - 5/8"	7 - 1/2"
3"	48mm	6mm	7 - 3/4"	7 - 1/4"	16 - 5/8"	7 - 1/2"
4"	49mm	6mm	8 - 3/4"	8 - 1/2"	18 - 1/4"	7 - 1/2"
5"	52mm	8mm	9 - 3/4"	10"	21"	9"
6"	54mm	8mm	10 - 3/4"	11"	23 - 3/8"	9"
8"	60mm	8mm	12 - 1/2"	13 - 1/4"	27"	10"
10"	64mm	10mm	15"	16"	31 - 5/8"	11"
12"	70mm	12mm	18"	18"	37 - 1/4"	14"
14"	75mm	12mm	22"	21"	48"	18"